



**WATER-BASED
POPCORN CEILING TEXTURE SPRAY**

DESCRIPTION AND USES

Zinsser® Water-Based Popcorn Ceiling Texture Spray is designed to create a popcorn texture quickly and easily. This low-odor, water-based formula creates professional results quickly. Water-Based Popcorn Aerosol is easy to apply and easy to clean. It is great for repairs and patches on already textured ceilings.

FEATURES

- Controlled spray
- Fast dry
- Repairs damaged texture

PRODUCTS

SKU (14 oz.)	Description
306195	Bright White Popcorn Texture Spray

PRODUCT APPLICATION

PAINTING CONDITIONS

Use in a well ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from overspray.

SURFACE PREPARATION

Complete any necessary surface repairs. For best results, prime and seal the surface before painting.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

TESTING SPRAY PATTERN

Practice spraying texture onto cardboard or scrap drywall to determine the best technique that delivers the desired pattern.

APPLICATION

Shake can vigorously for one minute before spraying. Also shake occasionally throughout use. Hold can upright 14-20" from surface and begin spraying in a quick back and forth motion that covers the surface and matches the surrounding texture. Keep the can in motion while spraying. Note: If the product output or pressure slows, shake the can and then continue the application. If problems still persist, put the can under running hot water to improve the spray performance. **Do not use near open flame.**

DRY & RECOAT TIMES

Dry times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 5-10 minutes and to handle in 10-15 minutes. Allow to dry for 24 hours before painting. Heavier textures may take more time to dry.

CLEAN-UP

After use, turn can upside down and press spray nozzle until the spray mist is clear to prevent clogging. Wipe off tip before storing. Clean-up wet paint with water. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse it in water. Do not stick a pin or other objects into the valve stem.

**TECHNICAL DATA****WATER-BASED POPCORN CEILING TEXTURE SPRAY****PHYSICAL PROPERTIES**

		WATER-BASED POPCORN CEILING TEXTURE SPRAY
Resin Type		Ethylene-vinyl Acetate Copolymer
Pigment Type		Titanium Dioxide, Calcium Carbonate, Talc
Solvents		Dimethyl Ether, Water
MIR		0.1 Max
Fill Weight		14 ounces
Recommended Dry Film Thickness (DFT) per Coat		Varies depending on porosity and size of popcorn texture
Practical Coverage at Recommended DFT (assume 15% material loss)		Covers up to 5 sq.ft./can
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	5-10 minutes
	Handle	10-15 minutes
	Topcoat	24 hours
Shelf Life		2 years
Flash Point		-42°F (-41°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.